

ISUZU D-MAX 3.0 Ddi LS 4x4 A/T

ENGINE	
Engine Code	4JJ3
Displacement (cc)	2999
No. of Cylinders	4
Compression Ratio	16.3:1
Bore X Stroke (mm)	95.4 x 104.9
No. of Valves	16
Power (kW) @ r/min	140 @ 3600
Torque (Nm) @ r/min	450 @ 1600-2600
Turbocharger	Standard
800 mm Water Depth Protection	Standard
Pre-Air Cleaner	Standard
ACG (90 A)	Standard
ACG with Intelligent Battery System (IBS)	Standard
Intercooler	Standard

7.8
206
Diesel

Transmission Type	6-Speed Automatio
Gear Ratio: 1st	3.6
Gear Ratio: 2nd	2.09
Gear Ratio: 3rd	1.488
Gear Ratio: 4th	1.000
Gear Ratio: 5th	0.687
Gear Ratio: 6th	0.58
Gear Ratio: Reverse	3.732
4WD Selector	Standard
Low Range Ratio	2.482

FRONT DIFFERENTIAL	
Shift on the Fly up to 100 km / hour	Standard
Axle Ratio: Final Drive	4.1

REAR DIFFERENTIAL	
Differential Lock	Standard
Axle Ratio: Final Drive	3.727

CHASSIS DESIGN	
Front Wheel Suspension	High Mounting
Rear Wheel Suspension	Leaf Spring Overslung
Shock Absorbers	Twintube Gas Pressurised
Suspension	High-Ride
Skid Plate Guard Front	Standard
Skid Plate Guard Rear	Standard
Transfer Case Guard	Standard
Oil Pan Guard	Standard

WHEELS AND TYRES	
Tyre Size	255 / 65 R 17 AT
Wheels Size / Type	Alloy 17" x 7.0J-33
Spare Wheel Size / Type	17" X 7.0J-33 Steel
Turning Circle (m)	12.5
Tyre-Pressure Monitoring Sensor	-

DIMENSIONS	
Length (mm)	5 325
Width (mm)	1 870
Height (mm)	1 780
Wheelbase (mm)	3 125
Front / Rear Track (mm)	1 570 / 1 570
Rear Overhang (mm)	1 310
Ground Clearance (mm)	227
Loadbox Length (mm)	2 330
Loadbox Width (mm)	1 590
Loadbox Depth (mm)	465
Approach Angle (°)	30
Departure Angle (°)	24
Breakover Angle (°)	21.4
Wading Depth (mm)	800

MASS / CAPACITY	
Gross Axle Mass – Front (GA1) (kg)	1 450
Gross Axle Mass – Rear (GA2) (kg)	1 910
Gross Vehicle Mass (GVM) (kg)	3 100
Gross Combined Mass (GCM) (kg)	6 000
Tare Mass (kg)	1875
Payload (kg)	1165
Towing Capacity (kg): Unbraked Trailer²	750
Towing Capacity / Rating (kg): Braked Trailer²	3 500
Fuel Tank Capacity (Litres)	76

LOADBOX FEATURES	
Tiedown Brackets in Loadbox for Load Restraint	4
Rope Hooks on Loadbox Side	Standard

Standard
Standard
-
Standard
-
Driver and Passenger
Passenger
Standard
_
-
-
-
Standard
Standard
Standard
-
-
-
Standard
Standard

SECURITY FEATURES	
Manual Door Locks	-
Remote-Controlled Central Locking	Standard
Remote Keyless Entry	Standard
Passive Entry Start System (PESS)	_
Child-Proof Rear Door Locks	_
Anti-Theft Alarm System	Standard
Ultrasonic Alarm	Standard
Transponder Immobiliser System	Standard
Selectable Door Unlock	Standard
Walk-Away Auto Door Lock	_

INTERIOR / EXTERIOR LIGHTING		
Front Reading Lamps	Standard	
Interior Courtesy Lamps	Standard	
Illuminated Entry	Standard	
Front Fog Lamps	Standard	
Daytime Running Lights (DRL)	Standard	
Headlamps	Halogen	
Headlamp Levelling	Standard	
Headlamps 'ON' Warning Buzzer	Standard	
Turn Indicator Lamp on Door	-	
Rear Taillights, Combination	Bulb	
High-Mounted Centre Stop Lamp	Standard	
Follow-Me-Home Headlamps	Standard	

Front Wiper	Variable Intermittent
Radiator Grille	Grey
Front Bumper	Body Colour
Rear Bumper	Black
Towbar	Accessory (3.5T)
Exterior Door Handle	Body Colour
Exterior Mirror	Body Colour, Power Adjustment and Manua Folding, Side Indicator, Driver Side Aspherical
B-Pillar Blackout	-
Roof Rails	-
Sports Bar	-
Side-Steps	-
Mudflaps	Front and Rear
Tailgate Handle	Body Colour
Cab Protector	

INTERIOR FEATURES Power-Assisted Steering (PAS)	Hydraulic
Air Conditioning	Manual
Pollen Filter	Standard
Inside Rear-View Mirror	Day / Night
Sunvisor	Driver with Ticket Holder, Passenger wit Vanity Mirror
Overhead Console with Map Lamps (X2) and Sunglasses Holder	Standard
Digital Clock	Standard
Cruise Control	Standard
Multi-Information Display (MID)	
Dashboard Illumination Control	Standard
Power Socket, Auxiliary 12V lP Mounted	1
Cigarette Lighter	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard
Steering Column Adjustment	Tilt and Telescopic
Steering Wheel Trim	Urethane
Steering Wheel Multi-Functional Controls	Audio & Auto Cruise
Gear Shift Trim	Urethane
Front Seat Configuration	Bucket Seats (x2)
Rear Seat Configuration	-
Seat Trim	Cloth
Seat Adjustment	6-Way Manual Driver
Storage Pockets behind Front Seats	-
Door Trim with Storage Pockets and Integrated Cupholders	Standard
Interior Door Release Handle	Black
Interior Trim Colours	Pale Grey Upper / Black Lower
A-Pillar Assist Grip, Driver and Passenger	Standard
Roof-Mounted Assist Grips	Driver & Passengers
Floor Trim	Carpet with Heel Pac and Tibia Pad
Floor Tunnel Console with Integrated Cupholder	Standard
Centre Console Storage Box with Lid	Standard
Driver Footrest	Standard
Rear Heater Duct	-
Storage Box	-
Window Operation	Power Front with Driver One-Touch, Jam Protection and Timer
Rear Window	Fixed without Defogge
Fuel Flap Remote Opener	Standard
Ventilator Grille with Shutter (Fin Shut)	Standard

Audio System	AM/FM Radio, 7" Touch Screen, Bluetooth - Audio Streaming, Apple CarPlay & Android Auto WiFi & Handsfree Phone
USB Port (Music Playback and Device link)	Standard
Speakers	4
Antenna	Standard

OPTIONS	
17" Alloy Wheel	-
18" Alloy Wheel and 265 / 60 R 18 Tyre (All Terrain)	Available
18" Alloy Wheel and 265 / 60 R 18 Tyre (H/T Terrain)	Available
Differential Lock	-
Hubcap Steel Wheel	-
Hubcap Alloy Wheel	Available
Spare Tyre Steel	-
Spare Tyre Alloy	-
Sports Bar – Black	_
Sports Bar – Chrome	_
Rear Sliding Window	_
Safari Beige	Available
Partial Leather Seat with Manual Adjustment	_

WARRANTY / SERVICE INTERVALS		
Warranty and Roadside Assistance	5 Years / 120 000 km	
Anti-Corrosion Warranty	5 Years / Unlimited km	
Service Plan	5 Years / 90 000 km	
Service Intervals	12 Months / 15 000 km	

1 Fuel Economy and ${\rm CO_2}$ data as per ECE R101 / SANS 20101 regulation. Note that the actual fuel consumption will depend on many factors, including the driver's driving habits, prevailing conditions and the vehicle's equipment, condition and use.

2 Towing capacity subject to South African Road Traffic Act. The weight of the towing vehicle including trailer towball load must not exceed the Gross Vehicle Mass (GVM). The combined weight of the fully loaded vehicle and trailer must not exceed the Gross Combination Mass (GCM). Maximum individual axle loads (GA1 and GA2) must not be exceeded (e.g.: if a 3.0L Diesel is towing 3,500kg, its maximum Vehicle mass is 2,500kg in order to be within GCM).